

# X1000

**bolle**  
TACTICAL

Low profile double ballistic lens, the X1000 dual lens offers the best anti-fog resistance. Featuring equalizer technology which uses a waterproof, breathable vent to eliminate any moisture. The result is distortion free vision and no fogging at any altitude. With the X1000 dual lens, you will be completely protected and prepared for any situation

ref. X1NDEI



FAX1DEF



FAX1DEJ

Europe Bollé Safety  
95 Rue Louis Guérin  
69100 Villeurbanne - France  
tel: 00 33 (0) 4 78 85 23 64  
fax: 00 33 (0) 4 78 85 28 56  
contact@bolle-safety.com

U.K. Bollé Safety  
Unit C83 - Barwell Business Park  
Leatherhead Road - Chessington  
Surrey - KT9 2NY  
tel. 00 44 (0)208 391 4700  
fax 00 44 (0)208 391 4733  
e-mail : sales@bolle-safety.co.uk

**TACTICAL**

**Ballistic Resistance  
STANAG 2920**

**V50 : 990 km/h (275 m/s)**

www.bolle-safety.com

# X1000

Safety goggles

STANDARDS MARKINGS :

Products ref.	LENSES												FRAMES													
	Risks relating to radiations		Bollé Protection logo	Optical quality			Mechanical Risks			Electrical Risks	Thermal Risks	Coatings (Optional marking K: anti-scratch N: anti-fog)		CE logo	Bollé Protection logo	Standards	Chemical Risks			Electrical Risks	Mechanical Risks			Thermal Risks	CE logo	
	EN 170 - UV	EN 172 - Solar (100% UV)		Permanent wear	Intermittent wear	Short period	Low energy impact 45 m/s	Medium energy impact 120 m/s	High energy impact 190 m/s	Extreme temperature impact	Electric arc short circuiting	Molten metals and hot solids	anti-scratch				anti-fog	Liquid drops	Large dust particles > 5 microns	Gas and fine dust particles < 5 microns	Electric arc short circuiting	Low energy impact 45 m/s	Medium energy impact 120 m/s	High energy impact 190 m/s		Extreme temperature impact
X1NDEI	2C-1,2			1			B	N/A	T	N/A	N/A	K	N			EN 166	3				N/A	B	N/A	T	N/A	
FAX1DEI	2C-1,2			1			B	N/A	T	N/A	N/A	K	N		N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
FAX1DEJ	2C-1,2			1			B	N/A	T	N/A	N/A	K	N		N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
FAX1DEF		5-2,5		1			B	N/A	T	N/A	N/A	K	N		N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A

N/A: Non applicable



**Ballistic Resistance**  
**STANAG 2920**

PACKAGING AND EAN 13 CODE :

	X1NDEI
individual plastic bag	3660740005740
N/A	N/A
60 safety goggles per outer pack	3660740205744



FAX1DEF  
**V50 : 979 km/h (272 m/s)**

**V50 : 954 km/h (265 m/s)**



FAX1DEJ

CHARACTERISTICS :

Face	Ballistic outer lens: 2.95mm, anti-scratch - Curve 4.5 Ballistic inner lens: 1.3mm, anti-fog - Curve 5.75
Frame	Black TPV Available in black, sand and nato green
Spare Lenses	Clear, yellow and smoke tints
Strap	Adjustable, 40 mm wide with non-slip technology
Foam	No

PACKAGING AND EAN 13 CODE :

	FAX1DEI	FAX1DEJ	FAX1DEF
individual plastic bag	3660740005757	3660740005764	3660740005771
15 spare lenses per box	3660740105754	3660740105761	3660740105778
150 spare lenses per outer pack	3660740205751	3660740205768	3660740205775

Notified laboratories for certification :



Banc Officiel d'Épreuve Saint-Etienne

